

The future of medium-duty, powered by Mack.

Arriving late 2023. Pre-production model shown.


MD ELECTRIC

Max Payload 19,400

MAC

Estimated Range* 230 MILES Peak Torque* **1,850** LB.-FT. MAX

Meet the Mack MD Electric. Available in class 6 or 7 configurations, it's an all-electric medium-duty truck with all the capabilities and durability you expect from a Mack. With a focus on driver comfort and productivity, lower routine maintenance costs, and step-bystep integration, MD Electric combines everything you need to bring eMobility to your fleet.



MD ELECTRIC



Key Components

Batteries

Available with 2 or 3 NMC lithium-ion batteries (Lithium Nickel Manganese Cobalt Oxide), 394V, fast charge capability, 150 or 240 kWh capacity

Power Source

3-Phase permanent magnet synchronous motor with 138 kW (185 hp) continuous power

Charging System

CCS1 charging

Auxiliary Power ePTO 10 kW

Brakes 3-Mode regenerative

Performance and Specifications**

Charging Time and Rate AC Charging @ 19.2 kW 6-11 hours DC Charging @ 80 kW 100-160 minutes

Horsepower/Torque

185 Continuous Hp/960 lb.-ft. max 260 Peak Hp/1850 lb.-ft. max

Weight Rating (GVWR)

Available in class 6 or 7 configurations

Max Payload

19,400 lbs

Comfort

Standard Cab Air Suspension; Standard Air Ride Drivers Seat; Quiet Cab Insulation

Service and Training Supported through the Mack dealership network

Estimated Range 230 miles

Axles Meritor front and rear axles

Wheelbase Options 206 in, 221 in, 236 in, 251 in, 270 in

Get support to go electric.

Our step-by-step integration process makes it easy to plug the MD Electric into your business.



©2023 Mack Trucks, Inc. All rights reserved. Mack, Mack and the Bulldog design, Bulldog and all other marks contained herein are registered trademarks of Mack Trucks, Inc. and/or Mack Trucks, Inc. affiliated companies. All other marks contained herein are the property of their respective owners. All terms and conditions on this sheet are based on the latest product information available at the time of publication. Mack Trucks, Inc. reserves the right to make any changes at any time, without notice.

*Based on Mack internal testing. Actual range, motor output, and charge times may vary based on battery condition, charger output, and environmental factors. **Performance varies by application, vehicle configuration and route conditions.



206 in

270 in